# **Cold Water Gasoline Belt Drive**

The popular CBA Series of pressure washers features a lightweight aluminum frame, base plate and belt guard making it one of the most lightweight, yet industrial-quality models in the industry. The patented vibration isolation plate is designed to absorb vibration and noise and will reduce movement of the unit while it is running.

## **CBA Aluminum Series**



General pumps feature an external bypass system which allows more water into the system to protect from heat build-up



Patented vibration isolation plate with four rubber isolators for reduced movement



### **Pump**

- Belt drive triplex piston AR or General pump with ceramic plungers
- Stainless-steel and brass unloader with adjustable pressure
- Forged brass manifold
- Thermal relief valve
- Water filter with clear sleeve for screen inspection

- Performance-proven engine with low-oil protection

- Light, corrosion resistant aluminum frame
- 1-inch aluminum tube handles for easier pulling
- Aluminum base plate
- Two-piece belt guard for quick access to belts
- Solid %-inch diameter full-length threaded axle
- Pneumatic tires with tubes for longer life
- Dual rubber isolators

## Component

- Dual cogged belt drive system for increased belt life

## **Unit Includes**

- Quick connect nozzles (0°, 15°, 25° and 40°)
- 50-foot x %-inch non-marking hose with quick connects, swivel and bend restrictors
- Professional-grade insulated trigger gun with safety lock-off
- 48-inch lance with rubber grip

## Warranties







<b>Model Number</b>	PSI	<b>GPM</b>	Displacement/Engine	Dimensions (LxWxH)	Ship Wt.	Net Wt.
CBA-3504-0MHB	3500	3.7	389cc Honda OHV	47in.x27.5in.x28.5in.	215 lbs.	165 lbs.
CBA-3504-0MRB	3500	3.7	404cc Subaru OHC	47in.x27.5in.x28.5in.	215 lbs.	165 lbs.
CBA-3504-1MHB*	3500	4.0	389cc Honda OHV	47in.x27.5in.x28.5in.	215 lbs.	165 lbs.
CBA-4004-0MHB	4000	3.4	389cc Honda OHV	47in.x27.5in.x28.5in.	215 lbs.	165 lbs.
CBA-4004-0MRB	4000	3.4	404cc Subaru OHC	47in.x27.5in.x28.5in.	215 lbs.	165 lbs.
CBA-4004-1MHB*	4000	3.5	389cc Honda OHV	47in.x27.5in.x28.5in.	215 lbs.	165 lbs.

\*Model comes standard with external bypass system and General pump.

## ACCESSORIES & OPTIONS

Additional to the state of the							
<b>Part Number</b>	Description	Fits Models					
50-0161	High pressure detergent injection - High pressure water mixes with detergent to clean even the heaviest build-up	All models					
AW-8400-0021	Low pressure detergent injection - Allows the user to apply the recommended detergents	All models					
	Insulated dual lance - Has both a high and low pressure tip that allows you to switch to the low pressure chemical injector without having to change tips	All models					
CX-0082	External bypass system - Allows more water into the system to protect from heat build-up; attaches to the pump	All models except 1MHB					
TX-1302-W	Puncture-proof tires - Tires are flat-free and maintenance-free, 13-inch, white hub, two tires	All models					