

# Cold Water Electric Belt Drive

## CW Premium Series


The electric version of the CW Series offers up to 5000-PSI of cleaning power. Perfect for heavily-soiled commercial and industrial equipment that requires indoor cleaning, electric pressure washers are much quieter than gas models and there is no need to worry about proper ventilation because of exhaust fumes. With a 7 year pump warranty, you know this unit is built to last.



CW-3004-4ME3




NEMA L15-30P,  
30-amp plug



NEMA 15-50P,  
50-amp plug



NEMA 6-50P,  
50-amp plug



External bypass system allows more water into the system to protect from heat build-up

### Pump

- Belt drive triplex piston General pump with ceramic plungers
- Stainless-steel and brass unloader
- Forged brass manifold
- Thermal relief valve
- Water filter with clear sleeve for screen inspection

### Motor

- Totally enclosed fan-cooled electric motor with thermal overload protection
- 10-foot power cord

### Frame

- Powder coated steel tube handles and base plate
- Totally enclosed powder coated steel belt guard
- Convenient gun/wand holder and hose wrap
- Solid steel threaded axle
- Pneumatic tires with tubes for longer life
- Dual rubber isolators

### Component

- Heavy-duty dual cogged belt drive system for increased belt life

### Unit Includes

- Quick connect nozzles (0°, 15°, 25° and 40°)
- 50-foot x 3/8-inch non-marking hose with quick connects, swivel and bend restrictors
- Professional-grade insulated trigger gun with safety lock-off
- 36-inch lance with rubber grip (48-inch on 4000 & 5000-PSI models)

### Warranties



Model Number	PSI	GPM	HP/Motor	Plug Type	Dimensions (LxWxH)	Ship Wt.	Net Wt.
CW-2405-4ME1	2400	4.6	7.5 HP, 230V, 1Ø, 35.7A	NEMA 6-50P	46in.x28in.x30in.	345 lbs.	333 lbs.
CW-2405-4ME3*	2400	4.6	8.0 HP, 230V, 3Ø, 24.7A or 8.0 HP, 460V, 3Ø, 11.5A	NEMA L15-30P	46in.x28in.x30in.	255 lbs.	243 lbs.
CW-3004-4ME1	3000	3.5	7.5 HP, 230V, 1Ø, 35.0A	NEMA 6-50P	46in.x28in.x30in.	350 lbs.	338 lbs.
CW-3004-4ME3*	3000	3.5	8.0 HP, 230V, 3Ø, 23.0A or 8.0 HP, 460V, 3Ø, 11.5A	NEMA L15-30P	46in.x28in.x30in.	330 lbs.	318 lbs.
CW-3005-0ME1	3000	4.8	10.0 HP, 230V, 1Ø, 37.5A	NEMA 6-50P	45.5in.x32.5in.x30in.	470 lbs.	396 lbs.
CW-3005-0ME3*	3000	4.8	10.0 HP, 230V, 3Ø, 25.6A or 10.0 HP, 460V, 3Ø, 12.8A	NEMA 15-50P	45.5in.x32.5in.x30in.	450 lbs.	376 lbs.
CW-4004-0ME3*	4000	3.9	15.0 HP, 230V, 3Ø, 40.0A or 15.0 HP, 460V, 3Ø, 20.0A	NEMA 15-50P	45.5in.x32.5in.x30in.	505 lbs.	431 lbs.
CW-5004-0ME3*	5000	4.0	15.0 HP, 230V, 3Ø, 40.0A or 15.0 HP, 460V, 3Ø, 20.0A	NEMA 15-50P	45.5in.x32.5in.x30in.	505 lbs.	431 lbs.

\*460V motors available as no-cost options.

### ACCESSORIES & OPTIONS

Part Number	Description	Fits Models
50-0161	High pressure detergent injection - High pressure water mixes with detergent to clean even the heaviest build-up	All models
AW-8400-0021	Low pressure detergent injection - Allows the user to apply the recommended detergents	All models
CX-0003	460V, 3-phase models - For when you have 460V of power available	CW-2405-4ME3 & CW-3004-4ME3 models
CX-0005	Insulated dual lance - Has both a high and low pressure tip that allows you to switch to the low pressure chemical injector without having to change tips	All models
CX-0057	460V, 3-phase models - For when you have 460V of power available	CW-4004 to CW-5004 models
CX-0062	460V, 3-phase models - For when you have 460V of power available	CW-3005-0ME3
TX-1302-W	Puncture-proof tires - Tires are flat-free and maintenance-free, 13-inch, white hub, two tires	All models